

HOS - SERIES

HORIZONTAL OPEN-WELL SUBMERSIBLES - PREMIUM RANGE



m ³ /hr	0	15	18	21	24	27	30	33	36	39	42	45
l/min	0	250	300	350	400	450	500	550	600	650	700	750
m ³ /hr	0	30	33	36	39	42	45	48	54	60	66	72
l/min	0	500	550	600	650	700	750	800	900	1000	1100	1200
m ³ /hr	0	42	45	48	51	54	57	60	66	72	78	-
l/min	0	700	750	800	850	900	950	1000	1100	1200	1300	-
m ³ /hr	0	54	57	60	66	72	78	84	90	96	102	108
l/min	0	900	950	1000	1100	1200	1300	1400	1500	1600	1700	1800

PRODUCT CODE	MODEL	PHASE	HP	KW	OUTLET in mm	CODE	TOTAL HEAD IN METERS											
H3P2022NTSM5BM1CC01	DH30MH	T	3	2.2	65	B	23	20	19.5	19	18.5	18	17.5	16.5	14.5	13	11.5	-
H3P2022NTSM5AH1CC01	DH30HH	T	3	2.2	50	A	25	-	-	-	22	21.5	20	19	18	16	-	-
H3P2022NTSM5AP1CC01	DH30PH	T	3	2.2	50	A	33	30	29	28.5	28	24.5	23.5	22	18	-	-	-
H3P2037NTSM5CL1CC01	DH50LH	T	5	3.7	80	C	28	25	24	23.5	23	22.5	22	21.5	20	18.5	16	-
H3P2037NTSM5CM1CC01	DH50MH	T	5	3.7	65	C	30	26.5	26	25.5	24.5	23	22.5	20	19	18	-	-
H3P2037NTSM5BH1CC01	DH50HH	T	5	3.7	50	B	32	-	30	29.5	29	28	27	26	24.5	22	19.5	16
H3P2037NTSM5AP1CC01	DH50PH	T	5	3.7	50	A	46	44	43	42	41	40	38	34	32	28.5	24.5	21
H3P2045NTSM5DL1CC01	DH60LH	T	6	4.5	80	D	28	24	23.5	23	22	20	18	16	-	-	-	-
H3P2045NTSM5BM1CC01	DH60MH	T	6	4.5	65	B	33	-	-	-	30	29	28	26	25	23	20	-
H3P2045NTSM5BH1CC01	DH60HH	T	6	4.5	50	B	37	-	35	34	33	31	29	27	25	23	-	-
H3P2045NTSM5AP1CC01	DH60PH	T	6	4.5	50	A	48	-	-	-	44	42	40	37	34	30	27	23
H3P2055NTSM5DL1CC01	DH75LH	T	7.5	5.5	80	D	29	26.5	26	25.5	24.5	23	22.5	20	19	18	14.5	13
H3P2055NTSM5BM1CC01	DH75MH	T	7.5	5.5	65	B	36	34	33	32.5	31.5	31	30	29	27	24.5	22.5	19.5
H3P2055NTSM5BH1CC01	DH75HH	T	7.5	5.5	50	B	44	40	39	37.5	36	34.5	33	31.5	27.5	23	-	-
H3P2055NTSM5AP1CC01	DH75PH	T	7.5	5.5	50	A	51	-	48.5	47	46	45	43	41	38	37	33	28