

VOS - SERIES

VERTICAL OPEN-WELL SUBMERSIBLES - PREMIUM RANGE

m ³ /hr		0	4.5	6	7.5	9	10.5	12	13.5	15	16.5	18
l/min		0	75	100	125	150	175	200	225	250	275	300
m ³ /hr		0	6	9	12	15	18	21	24	27	30	36
l/min		0	100	150	200	250	300	350	400	450	500	600
m ³ /hr		0	12	18	24	30	36	42	48	54	60	-
l/min		0	200	300	400	500	600	700	800	900	1000	-
m ³ /hr		0	36	48	60	72	84	96	108	120	132	-
l/min		0	600	800	1000	1200	1400	1600	1800	2000	2200	-



PRODUCT CODE	MODEL / STAGE	PHASE	HP	KW	OUTLET in mm	CODE	TOTAL HEAD IN METERS											
V2P2022N**M5CR06C*01	3DO/1	T	3	2.2	75	C	29	26	25	23	21	19	16	13	10	-	-	
V2P2022N**M5EM09CG01	3DAM/1	T	3	2.2	125	E	19	13	12	11	10	8	6	-	-	-	-	
V2P2022N**M5CR06C*02	3DT/2	T	3	2.2	65	C	41	39	34.5	31	26	20	14	8	-	-	-	
V2P2022UTSM5CR06C*02	3DT-R(O)/2	T	3	2.2	65	C	41	39	34.5	31	26	20	14	8	-	-	-	
V2P2022N**M5BR04C*03	3DE/3	T	3	2.2	50	B	62	57	55	52	50	42	34	23	16	-	-	
V2P2037N**M5CR06C*01	5DO/1	T	5	3.7	75	C	28	-	-	26	25	24	22	20	17	12	-	
V2P2037N**M5EM09CG01	5DAM/1	T	5	3.7	125	E	21	17	16	15.5	14.5	14	12	11	9	7	-	
V2P2037N**M5CR06C*02	5DT/2	T	5	3.7	65	C	47	-	43	41	37	33	26	18	-	-	-	
V2P2037UTSM5CR06C*02	5DT-R(O)/2	T	5	3.7	65	C	47	-	43	41	37	33	26	18	-	-	-	
V2P2037N**M5BR06C*03	5DE/3	T	5	3.7	50	B	62	60	59	58	56	55	52	49	46	40	29	
V2P2037N**M5AR04C*04	5DQM/4	T	5	3.7	50	A	85	77	76	74	72	68	64	59	52	34	-	
V2P2037N**M5BR06C*04	5DQ/4	T	5	3.7	50	B	70	65	63	61	59	57	54	50	45	39	28	
V2P2037N**M5AR04C*06	5DX/6	T	5	3.7	50	A	125	116	110	104	98	89	80	69	52	29	-	

** - Available in Three Phase "TS" (DOL) & "TD" (SD)
* - Available with "C" (Cast Iron) & "G" (Gun Metal) Impellers

VOS - SERIES

VERTICAL OPEN-WELL SUBMERSIBLES - PREMIUM RANGE

m ³ /hr	0	4.5	6	7.5	9	10.5	12	13.5	15	16.5	18
l/min	0	75	100	125	150	175	200	225	250	275	300
m ³ /hr	0	6	9	12	15	18	21	24	27	30	36
l/min	0	100	150	200	250	300	350	400	450	500	600
m ³ /hr	0	12	18	24	30	36	42	48	54	60	-
l/min	0	200	300	400	500	600	700	800	900	1000	-
m ³ /hr	0	36	48	60	72	84	96	108	120	132	-
l/min	0	600	800	1000	1200	1400	1600	1800	2000	2200	-

PRODUCT CODE	MODEL/ STAGE	PHASE	HP	kW	OUTLET in mm	CODE	TOTAL HEAD IN METERS														
							0	4.5	6	7.5	9	10.5	12	13.5	15	16.5	18				
V2P2045N**M5CR06C*02	6DT/2	T	6	4.5	65	C	46	45	43	40	37	34	30	25	20	-	-				
V2P2045NTDM5AR04CC05	6DVM/5	T	6	4.5	50	A	95	93	91	90	87	84	80	77	72	68	63				
V2P2045N**M5AR04C*07	6DSM/7	T	6	4.5	50	A	145	140	129	122	114	104	93	80	61	34	-				
V2P2056N**M5EM09CG01	7DAM/1	T	7.5	5.5	125	E	25	22	21	20	19	18	16	15	13	12	-				
V2P2055N**M5ER06C*01	7DOK/1	T	7.5	5.5	75	E	29	-	26	23	21	18	12	-	-	-	-				
V2P2055N**M5CR06C*02	7DT/2	T	7.5	5.5	65	C	51	-	49	47.5	46	42.5	38.5	34	28	21.5	-				
V2P2055N**M5CR06C*03	7DE/3	T	7.5	5.5	65	C	67	62	59	54.5	49.5	42.5	31	21	-	-	-				
V2P2055N**M5AR04C*04	7DQM/4	T	7.5	5.5	50	A	106	-	100	96	94	92	88	84	80	75	-				
V2P2055N**M5BR06C*04	7DQ/4	T	7.5	5.5	50	B	80	-	74	72	69	65	62	58	53	40	-				
V2P2055N**M5BR04C*05	7DV/5	T	7.5	5.5	50	B	100	97	96	94	92	90	88	84	78	73	70				
V2P2055N**M5AR04C*06	7DX/6	T	7.5	5.5	50	A	120	116	112	110	109	106	102	99	93	87	84				
V2P2055N**M5AR04C*06	7DXM/6	T	7.5	5.5	50	A	136	128	121	118	110	103	92	84	70	56	-				
V2P2055N**M5AR04C*07	7DSM/7	T	7.5	5.5	50	A	145	-	133	130	123	112	94	80	66	-	-				
V2P2055N**M5AR04C*09	7DIM/9	T	7.5	5.5	50	A	188	174	165	156	147	134	120	103	78	44	-				

** - Available in Three Phase "TS" (DOL) & "TD" (SD)
 * - Available with "C" (Cast Iron) & "G" (Gun Metal) Impellers

